

Concrete Vibrator LXT®

DVR350RTE

18V • 800 mm • 13 000 min⁻¹

An 800 mm shaft for easy air pocket removal

Battery-operated 18V vibrating poker. Suitable for quick and easy removal of air pockets from concrete in foundations and bases. Shaft length 800 mm and diameter 25 mm.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Vibrations per minute	13000 min ⁻¹
Vibrator Shaft Length	0,8 m
Vibrator Shaft Diameter	25 mm
Product net weight	2,4 kg
Sound Pressure Level (L _{pA})	≤ 70 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Tool weight with battery	2,9 - 3,3 kg
Product Dimensions (L x W x H):	1083 x 93 x 250 mm
Vibration Level, Load with Flexible Hose	8,0 m/s ²
Vibration Uncertainty (K Factor), Load with Flexible Hose	1,5 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²

EAN 0088381813853

Link to product - www.makita.com

User benefits

- Quick and effortless vibration of foundations
- Protective cover on switch and battery minimizes contamination
- Ergonomic soft grip handle provides increased comfort
- Battery protection circuit protects against overloading, over-discharging and over-heating



Related products

Standard AC

450128-8 (2x)

Battery cover, LXT®, 14,4 – 18V



821766-7

Plastic Carrying Case



Standard MA

BL1850B (2x)

Battery LXT® 5,0 Ah



DC18RC

Battery Charger LXT®



Optional AC

821766-7

Plastic Carrying Case



Other

[User manual](#)

[Parts drawing](#)